

Lux Matt

Matt protective wax for parquet

Matt protective wax based on hard waxes and polymers for the maintenance and protection of lacquered and oiled wooden floors. Recommended for the periodic maintenance of lacquered or oiled wooden floors, both natural and coloured. It is streak-free.

Technical data 20 °C – 60% R.H.

Appearance	White liquid
Density	1.00 kg/litre
pH	8
Ready for traffic	1 hour
Indicative yield	About 30 m ² /litre
Application temperature	From + 5 to + 35 °C
Storage	24 months in original sealed packaging – Frost sensitive
Packaging	1 litre bottles

Instructions for use

Remove dust and impurities from the surface with a broom or vacuum cleaner. Wash the floor with a suitable cleanser, such as Pulito Parquet, Deteroil or Saniparquet and let it dry. Spread the wax evenly using a soft cloth moistened with water and well wrung. If necessary, apply a second coat after about 1 hour. In the case of oil finished floors wait 15 – 20 days after oil finishing before carrying out the treatment with Lux Matt.

Notes

- Always use only moistened and well wrung out cloths, avoiding excess of water.
- Shake before using.
- Do not exceed the quantity of product applied.

Safety regulations

Product for professional use. Strictly comply with what is stated on the label and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the local legislation in force.



Cleaning & Maintenance

Lux Matt



Certifications



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use. Rev 08 – 14/06/2024. This technical data sheet replaces the previous one..